

POWER STATION pe5010-W

Output power:	16 - 100 kW	Typical applications:	
DC current:	4000 - 8000 A (max. 8000 A / 4 V)	Chrome plating	Barrel plating
DC voltage:	2 - 24 V (max. 24 V / 4000 A)	Anodizing/Aluminium colouring	Rack plating

Water cooled DC power supply in switch mode technology, designed for the direct installation at the electroplating tank.



POWER STATION pe5010-W, front view

Characteristic values

Linearity inaccuracy:
- for amperage < 1 %
- for voltage < 0.5 %

Ripple less than < 2 %

Efficiency typical > 85 %

Powerfactor $\cos \varphi$ 0,95

Constant current and voltage control

Soft start function

Over temperature protection

Internal shunt with 60 mV at I_{nenn}

Pulse operation optional

Mains supply: standard 3 x 400 V +/- 10 % / 50-60 Hz
(other voltages on request)

Cooling

Water cooled / cooling water specification: see page 2

Ambient temperature 40°C (other on request)

Stainless steel cooling system, over temperature protected

Design

Compact Rittal TS cabinet; protection grade: IP54

Powder coated, RAL 7035

Mains supply below in cabinet

Cooling water connection in the plinth, 1/2" connections

DC connector in top of the cabinet



With mains power switch, fuses and sub distributor

Dimensions (W x H x D) 600 x (2200+150) x 600mm incl. plinth

EMV: EN50011 class A, group B ; EN61000-6-4 and EN61000-6-2;
CE-conformity low voltage guide line: EN50178

Values	Standard sizes - DC output ¹										¹ other sizes on request
	8000 A		7200 A				6500 A	5500 A	5000 A	4000 A	
DC current	8000 A		7200 A				6500 A	5500 A	5000 A	4000 A	
DC voltage	4 V	5 V	6 V	8 V	10 V	12 V	15 V	18 V	20 V	24 V	
Mains supply	3 x 400V AC										
Weight	approx. 300-380 kg										

Standard dimensions



Cooling water specification

For the water cooling system, city water with the following specifications should be used:

ph Value:	7,0 - 8,0	Inlet temperature:	18-26°C
Hardness:	<=1,3 mmol/l (<=7°dH)	Water pressure:	> 2bar
Chloride:	<=100 mg/l		

To operate this rectifier, and to keep the specified values of the cooling water, a closed cooling system is recommended.

Control

Standard: peRB-interface

Optional: external control via analog signals, also with integrated isolation amplifier

Signals: 0-10V
0-1V
4-20mA
0-20mA (other on request)

Control unit pe280
for the controlling of
DC power supplies of
the series POWER STATION pe5010-W

Designed for electroplating applications
Large 3-line LCD-display,
polycarbonate-keypad for easy operation
Current and voltage infinitely adjustable
by UP / DOWN buttons
Current and voltage preset
Ampere-hour counter (totalizer)
Protection grade: IP54
Ambient temperature max. 40°C



Optional available functions

Preset counter, dosage counter *
Ramp function (start / stop ramp)
Timer function for ON / OFF *
Voltage / current alarm *
Operating hours counter
Chopper timer (pulse-capable rectifier type requested)
Pole changer function (mechanical / electronic) *
Programmable DC steps (14 individual steps) *
Extern ON
* Indication / alarm output

Control via: RS485, PROFIBUS, TCP/IP (other on request)

Technical equipment, design and features: subject to change! For further information please contact plating electronic GmbH.